



Office Address: Saltee Plaza, #614,6th floor,
1,khudiram Bose Sarani,Mall Road, Beside:
ILS Hospital, Nagerbazar, kolkata 700080

Phone: 9831042772

Email: rupesh@aquafiltration.com



RO MEMBRANE

Product Details

SIZES : 4" X 40 & 8" X 40

The RO membranes include membranes of both 4" & 8" used for Brackish water with maximum TDS of 8000ppm. We are the distributor for Eastern Region . we can also provide membrane for Sea Water, Brackish water, Low fouling & Speciality on request with attractive prices and delivery.

We are supplying RO membrane which is a type of semi-permeable membrane that is used to ensure a proper passage of water molecules. The reverse osmosis membrane

is very important in wastewater treatment units since it eliminates all types of dissolved salts, organics, bacteria, pyrogens, and other pollutants with high effectiveness.

PRODUCT RANGE

Brackish Water, Sea Water, Fouling Potential Water.

Brackish Water

Toray RO membranes (available in 4-inch, 8-inch, and 16-inch diameters) are used for municipal, industrial, and commercial applications.

Sea Water

Toray manufactures seawater RO membranes in 4, 8, and 16-inch diameters that can treat seawater or high salinity water sources with > 10,000 ppm. Our products are widely used for mega desalination plants, watermakers for private boats and commercial ships, and treating mining tailing water for reuse or discharge.

Fouling Potential Water

Toray's low fouling RO membranes effectively treat feed water types with high fouling tendency. Combined with our proprietary durable "D-family" membrane recipe for enhanced chemical tolerance, Toray's membrane elements offer one of the most reliable performance under challenging conditions. Ideal for wastewater treatment and water reuse applications.